

# INTERNAL FILLING STATIONS FOR DIESEL OIL DISTRIBUTION



## Mobile filling station for diesel oil 430 l, 900 l

- Tanks are portable and rigid enough to be placed on bodies of most lorries or vans which permits safe and ideal fuel transport for all users. Filling stations are an ideal device for fuel refilling into building and farm machinery. Tanks received ADR certificate and fully comply with appropriate regulations.
- Tanks are made of UV-stable polyethylene of middle density, they are colour fast, do not crack and they are not etched by the liquid stored in them. The tank is delivered as a complete unit, ready to be used immediately. Structure of tanks is simple and that is why their usage is very easy. All accessories including its delivery device are placed on the tank top and they are secured by means of lockable lid.
- Tested according to the European Agreement (ADR) which refers to the International Road Transport of Hazardous Goods, TM 430 Certificate No. 413/0/575 and TM 900 Certificate No. 448/0/1237.

### Standard equipment:

- 4 m hose, nozzle with closing valve.
- Suction hose with a filter.
- 2" intake (filler) neck with external thread.
- Digital flowmeter (measuring tolerance  $\pm 0.5$  %).
- Float fuel-level indicator.
- Ventilation protected from spill during the transport.
- Lockable lid protecting the service unit from unfavourable weather and from unauthorized personnel's access.
- Mobile filling station can be also delivered in 12 V or 24 V version with its pumping power of 35 l/min., or 230 V with its pumping power of 56 l/min.



CAPACITY (l)	DIMENSIONS l x w x h (m)	WEIGHT (kg)	TYPE (V)		
430	1.18 x 0.86 x 0.91	55	3344 (12 V)	3345 (24 V)	3346 (230 V)
900	1.41 x 1.05 x 1.21	98	3347 (12 V)	3348 (24 V)	3349 (230 V)

## Mobile pumping device for diesel oil with a pump

- Approved for transport for immediate consumption according to ADR.
- Container from polyethylene with integrated handle and handgrips.
- Filling neck with integrated bleeding and venting.
- Tyre tube wheels with a diameter of 300 mm suitable also for the field.
- Breakwater ensuring easier manual handling.
- Integrated nozzle holder.
- Integrated offsets for fixing with straps during transport.

### Type: 7212

self-suction electric pump 12 V, 25 l/min with automatic delivery nozzle with 3 m long delivery hose and 4 m long electric cable



Type: 7212



Type: 7213

### Type: 7213

manual pump 25 l/min, 3 m delivery hose with a manual valve

- 19/20 kg
- 1,000 x 590 x 430 mm
- 100 l

