



◀ Air-operated pump for lubricants

Type: 4973, 4974, 4975, 6434

- Suitable where lubricants are often used.
- Set contains: a truck, pneumatic pump, pressure membrane, dust lid, locknut, compressed air cleaning unit, delivery pressure hose 4 m, delivery nozzle with a chuck joint.
- Delivery 1,500 g/min.
- Max. pressure 40 MPa.
- Set is delivered without a vessel.
- Vessel can be bought additionally as accessories.
- Sets can be delivered for vessels ranging from 12 to 200 kg.

TYPE	VESSEL INNER DIAMETER (mm)	VESSEL CAPACITY (kg)
4973	240-280	12-20
4974	260-300	12-30
6434	340-385	50-60
4975	550-600	180-200

Manual lubricating pump ▶

Type: 6431

- Easy operation – capacity: 0.5 l.
- Suitable for all lubricants and fillings.
- Max. delivery: 400 Ba.
- The set consists of: lubricating press, 300 mm pressure hose, chuck clutch.



Grease press Type: 7513 ▼

New easy FILL 400 gets along without any spring mechanism. You simply insert a grease cartouche, place a grease tow piston and set it off. Thanks to a vacuum in the lubricator head the piston moves to the top all alone and smoothly. Thanks to the variable Stroke-principle the lubricator is operated easily with the lever minimum movement.



Technical data:

- Grease press connection on the delivery side: M 10 x 1
- Filling volume (cubic cm): 400
- Filling possibilities: 400 g grease cartouche, DIN 1284 (12 511), (12 514)
- Pumping pressure up to (bar): 400
- System burst pressure (bar): 900
- Grease press head burst pressure (bar): 1,200
- Grease press pipe wall thickness (mm): 1

Specifications:

- Grease tube M 10 x 1, 300 mm long
- Chuck grease coupling M 10 x 1
- Tow piston, 10 pieces
- Ergonomic handle, non-slipping, very good transmission system and manual lifting. The device processes NLGI 2 fats at 10 °C as a minimum.
- Cylindrical thread on the grease press tube is shock proof and enables quick and simple screwing on.
- Fast bleeding by turning the grease press tube by half a revolution.
- Designed for use in harsh conditions.

◀ Mobile lubricating pump

- Enables to use an original lubricating medium, independently of the power source.
- Set includes: lubricating gun, dust lid, pressure diaphragm, pressure hose 1.5 m, discharge head with a chuck clutch.
- Suitable for original media 15-20 kg, with the can internal diameter 240-270 mm.



Type: 4976

Mobile lubricating pump ▶

Type: 6700

- A device designed for lubrication.
- Includes a pump and a pumping tube 2.5 m with a termination.
- The device is filled manually into a bin of a volume of 13 l.
- The wheels enable easy handling.

☑ 13 l

