

INTERNAL FILLING STATIONS FOR DIESEL OIL DISTRIBUTION



Double-case filling stations

- Special double-case structure functioning as integrated trapping tub.
- Peripheral metal bracings ensure its mechanical resistance.
- Bottom structure equipped with offsets for easy handling with a fork lift.
- Station equipment:
Optical indicator of one internal tank damage, filling hole with TW connector and limit switch, bleeding valve, level indicator, electric pump 230 V with its delivery of 72 l/min, automatic delivery nozzle with a holder, delivery hose 4 m, Type: 7216 with 8 m delivery hose.
- Delivered in three variants:
 - variant without a cover to be used under the roof (indoor),
 - variant with a cover to be used outside (outdoor),
 - variant with a cover, flowmeter, winch for 8 m delivery hose to be used outside (outdoor).

| TYPE | DESCRIPTION | POWER (V) | CAPACITY (l) | OUTPUT (l/min) | DIMENSIONS w x d x h (mm) | WEIGHT (kg) |
|------|---|-----------|--------------|----------------|---------------------------|-------------|
| 7214 | Pumping device for diesel issue without cover for indoor use | 230 | 2,500 | 72 | 1,200 x 1,800 x 1,740 | 220 |
| 7215 | Pumping device for diesel issue with cover for outdoor use | 230 | 2,500 | 72 | 1,200 x 1,800 x 1,800 | 235 |
| 7216 | Pumping device for diesel issue with cover, flowmeter, winch for 8 m long delivery hose for outdoor use | 230 | 2,500 | 72 | 1,200 x 1,800 x 1,800 | 255 |

LARGE-VOLUME DOUBLE-WALLED FILLING STATIONS

- Outdoor filling station with double-walled design and large volume for dispensing diesel. The stations are available with the lid in three versions. They are equipped with a 230 V pump with an output of 72 l/min and can be delivered with other accessories. The station can be extended with an additional unit and thus increase the total volume of stored diesel.

Type Basic: 8152

- Version with a hinged lid and 4 m hose for outdoor use.

Type Premium: 8153

- Version with the K33 flow meter, filter with water separator, reel with 8 m hose and hinged lid for outdoor use.

Type Additional station: 8154

- Version with optical indicator, filling port for tanks, anti-spill indicator, vent valve, level indicator, suction hose with set for connection to the first tank.



| TYPE | DESCRIPTION | POWER (V) | CAPACITY (l) | OUTPUT (l/min) | DIMENSIONS w x d x h (mm) | WEIGHT (kg) |
|------|---|-----------|--------------|----------------|---------------------------|-------------|
| 8152 | Filling station for dispensing diesel with a lid for outdoor use | 230 | 5,000 | 72 | 2,400 x 2,300 x 1,850 | 205 |
| 8153 | Filling station for dispensing diesel with a lid, flow meter, filter with water, separator reel for 8 m dispensing hose for outdoor use | 230 | 5,000 | 72 | 2,400 x 2,300 x 1,850 | 230 |
| 8154 | Additional filling station for dispensing diesel with a lid for outdoor use | 230 | 5,000 | 72 | 2,400 x 2,300 x 1,850 | 201 |