

INTERNAL FILLING STATIONS FOR DIESEL OIL DISTRIBUTION



◀ Mobile filling station for diesel oil 430 l, 900 l

- The filling stations are portable and rigid enough to be placed on the beds of most trucks or vans, which allows users to transport fuel safely and legally in accordance with the ADR regulations for the International transport of dangerous goods.
- The tanks are made from UV-stabilized medium density polyethylene, with stable coloring, do not crack and are delivered complete, ready for immediate use.



Standard equipment:

- 4 m hose, nozzle with closing valve.
- Suction hose with a filter.
- 2" intake (filler) neck with external thread.
- Digital flowmeter (measuring tolerance $\pm 0.5\%$).
- Float fuel-level indicator.
- Ventilation protected from spill during the transport.
- Lockable lid protecting the service unit from unfavourable weather and from unauthorized personnel's access.
- Mobile filling station can be also delivered in 12 V or 24 V version with its pumping power of 35 l/min., or 230 V with its pumping power of 56 l/min.

CAPACITY (l)	DIMENSIONS l x w x h (mm)	WEIGHT (kg)	TYPE (V)		
430	1,180 x 860 x 910	55	3344 (12 V)	3345 (24 V)	3346 (230 V)
900	1,410 x 1,050 x 1,210	98	3347 (12 V)	3348 (24 V)	3349 (230 V)

Internal filling station – FuelMaster ▼

- Above-ground internal pump stations for diesel oil delivery with their capacity of 2,500, 5,000 or 9,000 litres.
- Double-case structure from a very high quality polyethylene, resistant to UV radiation.
- Thanks to its double-case structure they do not need any trapping tub or wet well.
- Simple installation in an open area without further requirements.

Standard equipment:

- Pump with output of 79 l/min.
- Digital flow meter K600 B/3.
- Dispensing hose 6 m.
- Automatic dispensing nozzle.
- Glass filter with water separator.
- Filling piping 2" located in the wall.
- Mechanical spill-stop.
- Fluid level sensor UNIRx (measuring in liters).
- Sensor for liquid leak between walls.
- Maximum level sensor GOK.
- LED light with motion sensor.

Other optional equipment available in our offer upon agreement:

- Flowmeter with a possibility of recording up to 1,500 users.
- Computer software enabling to create detailed reports as for fuel consumption.
- Pump with its delivery up to 100 l/min.
- Delivery hose 12 m long.
- Protective steel frame and other ...



Type: 3558



Type: 3556



Type: 3557

TYPE	VOLUME (l)	MAIN DIMENSIONS w x d x h (mm)	WEIGHT (kg)	PUMP OUTPUT (l/min)	DELIVERY HOSE LENGTH (m)
3556	2,500	2,460 x 1,460 x 1,850	250	79	6
3557	5,000	2,850 x 2,230 x 2,340	320	79	6
3558	9,000	3,250 x 2,450 x 2,950	490	79	6