


STEEL TRAPPING TUBS FOR TRANSPORT

Tested for leak tightness according to EN standard



◀ Pallets PS 15/2 a PS 15/4 with trapping tubs

- Intended for safe storage and transport of liquids harmful to environment.
- Installation in buildings or under a shelter.
- Solid steel structure enables stacking in two layers.
- Removable pillars reduce transport costs.
- Standard surface finish with paint can be replaced by hot-dip galvanizing at the customer's request.



Trapping tubs for transport ▲▶

- Suitable for 2 or 4 two-hundred litre barrels.
- Tub structure permits transport of pallets with barrels. Surface finish is solved by hot-dip galvanizing or coating in combination with hot-dip galvanized grating.

TYPE	NAME	SURFACE FINISH	MAIN DIMENSIONS (mm)	TRAPPING TUB VOLUME (l)	LOAD CAPACITY (kg)
1215	Pallet PS 15/2	coated	600 x 1,200 x 1,300	205	1,200
1216	Pallet PS 15/4	coated	1,200 x 1,200 x 1,300	300	1,200
3576	Tub for 2 barrels	coated	800 x 1,400 x 1,300	220	1,200
3576-Z	Tub for 2 barrels	zinc-coated	800 x 1,400 x 1,300	220	1,200
6085	Tub for 4 barrels	coated	1,400 x 1,400 x 1,300	235	1,200
6085-Z	Tub for 4 barrels	zinc-coated	1,400 x 1,400 x 1,300	235	1,200