

PUMPS, FAUCETS AND LEVEL INDICATORS



Type: 1283

Type: 1282




Hand pump fixed in the barrel.

Plastic pumps

- Capacity of plastic pumps reaches ca. 25 l/min. Attaching 2" screw thread of the pump is provided with jack nut to ensure firm connection with a barrel. Telescope suction hose provides the utilization also with barrels of 216.5 l capacity, including the barrels with plug in a casing.
- Hand pump Type: 1283 is suitable mainly for water and oil.
- Hand pump Type: 1282 is suitable for pumping organic solvents, petrol, diesel, fuel oil etc.
- After using it is necessary to take it out from liquid and rinse it.

Plastic faucets



Type: 1281



Type: 1280



Type: 7509



Type: 7005



Type: 7006

Metal faucets

- Enables safe pouring of oil products from barrels with 3/4" bung.
- Possibility of locking.
- Possibility to set outflow direction (Types: 7006, 7007).



Level indicator ▲ 3/4"

Type: 7514

- Float level indicator is designed for 200 l barrels.
- Material: plastic
- Connection: 3/4" thread

TYPE	NAME	MATERIAL	COUPLING SIZE
1282	Pump	nylon	2"
1283	Pump	polypropylene	2"
1280	Faucet	polyethylene	2"
1281	Faucet	polyethylene	3/4"
7509	Faucet	polyethylene	3/4"
7005	Faucet	metal	3/4"
7006	Faucet	metal	3/4"



Plastic adapters

- Enable use of pumps and barrel faucet with threads other than 2" TRI-SURE.

TYPE	NAME	MATERIAL	CONNECTION SIZE
0071	Adapter	polyethylene	2" plastic / 2" TRI-SURE
0072	Adapter	polyethylene	DIN 61 / 2" TRI-SURE
0073	Adapter	polyethylene	Mauser plastic / 2" TRI-SURE



Level indicators

Type: 7007 (horizontal)

- Indicate liquid level in barrels.
- Suitable for light oils and chemicals.
- Outflow faucet 3/4".

Material: metal and glass
Connection: 3/4"

Hand pump

Type: 4582

- For oil to SAE 50, self-lubricating, non-aggressive media.
- Suitable use for motor oil, machine oil, cutting oil each to SAE 50, fuel oil, diesel, paraffin, undiluted antifreeze.
- Two parts of suction tube, its length can be made longer.
- PVC delivery hose, 1,000 mm with plastic drain.

Material: galvanized
Sealing material: NBR
Connection: G2" outer
and M 64 x 4 inner

Application: for barrels 60/200/220 l
Suction tube length: 1,200 mm

12 l/min.



Metal pump for barrel

Type: 7003

- For pumping of petroleum product such as oil to SAE 90 and diesel.
- Suction using telescopic metal tube to the depth 480–900 mm.
- Suitable for barrels 60–220 l.

Material: metal
Connection: G2" and G6/4"

16 l/min.



Manual lever pump SIGMA

Type: 7280

- Intended for industrial use.
- Suitable for pumping of petrol, liquid coolants, antifreeze, diesel oil and oils up to viscosity SAE 140.

Material: cast iron, NBR, metal
Connection: G2" for barrels 200/220 l

28 l/min (stroke 0.25 l)

