

LUBRICATING SETS OIL SETS



◀ Air-operated pump for lubricants

Type: 4973, 4974, 4975, 6434

- Suitable where lubricants are often used.
- Set contains: a truck, pneumatic pump, pressure membrane, dust lid, locknut, compressed air cleaning unit, delivery pressure hose 4 m, delivery nozzle with a chuck joint.
- Delivery 1,500 g/min.
- Max. pressure 40 MPa.
- Set is delivered without a vessel.
- Vessel can be bought additionally as accessories.
- Sets can be delivered for vessels ranging from 12 to 200 kg.

TYPE	VESSEL INNER DIAMETER (mm)	VESSEL CAPACITY (kg)
4973	240-280	12-20
4974	260-300	12-30
6434	340-385	50-60
4975	550-600	180-200

Manual lubricating pump ▼

Type: 6431

- Easy operation, capacity: 0.5 l.
- Suitable for all lubricants and fillings.
- Max. delivery: 400 Ba.
- The set consists of: lubricating press, 300 mm pressure hose, chuck clutch.



▶ Mobile lubricating pump

Type: 6700

- A device designed for lubrication.
- Includes a pump and a pumping tube 2.5 m with an end piece.
- The device is filled manually into a tank of a volume of 13 l.
- The wheels enable easy handling.



☐ 13 l



◀ Grease press Type: 7513

- Lever press Easy Fill 400 with a lever mechanism without springloaded mechanism.
- The grease cartridge is inserted into the press. Trailing piston is then fitted and activated.
- Can be filled with cartridge 400 g, DIN 1284 (12 511), (12 514).
- Pumping pressure up to 400 bars.
- Variable Stroke-principle for easy operation with minimal lever movement.
- Designed for use in demanding conditions.



Type: 4976

◀ Mobile lubricating pump

- Enables to use an original lubricating medium, independently of the power source.
- Set includes: lubricating gun, dust lid, pressure diaphragm, pressure hose 1.5 m, discharge head with a chuck clutch.
- Suitable for original media 15-20 kg, with the can internal diameter 240-270 mm.

Mobile vacuum cleaner and discharger for oil ▼

Type: 6428

- Suitable for handling of used oils.
- Equipped with 90 l reservoir, level meter, pocket for basic tools and height adjustable collecting tube with a faucet of 20 l of capacity.
- After suction pressure is reached, approx. 65 l of oil, hovering from the vehicle can be started (oil temperature 70-80 °C).



Manual portable oil filler ▼

Type: 6427

- Set with a double-acting pump. Tank is equipped with a level indicator to check the fluid level in the tank.
- Filling funnel included in the price!

Parameters:
Sealing: NBR
Delivery hose length: 2 m
Delivery for 1 cycle using a lever: 220 g
Max. oil viscosity: 240 SAE

☐ 24 l



Electric suction unit for oil ▼

Type: 6430

- Suitable for suction of used oil.
- Electric suction (15 l/min.) with a suction hose (2 m).
- Manual or electric discharge.
- It contains 7 probes (3x flexible, 2x fixed, 1x for Mercedes, 1x for VW).
- Equipped with a plastic tank (20 l).

☐ 20 l

