

SPECIAL MATS

Floor grid

Type: 4152

- Do not impound water – the grid suitable to moist areas – drip grooves.
- Do not pick up dirt.
- Easier drying.
- Easy maintenance of areas.
- Higher feeling of culture, hygiene, cleanness and neatness.
- Easy connecting and disassembly facilitate the handling.
- Thermal insulating features; more comfort in the areas stepped on with bear feet.
- Eliminate the risk of the growing of molds, prevent the carrying over of dirt.
- LD-polypropylene material does not absorb liquids.
- Resistant to the majority of common chemicals.
- Suitable to showers, bathrooms, swimming pools or in laboratories.

Area 1 pc. 0.36 m²
 Weight 0.9 kg
 Material polyethylene
 Max. load 2.5 kg/cm²
 Heat resistance -10 °C – +60 °C



Work Deck Tile Blue

Type: 6479, 6480, 6481



- Plastic floor grids are designed to protect feet and spine of employees. Considering their resistance, the grids may be used in wide area of application. The grids may be interconnected by modules of 1,200 x 600 mm (height 25 mm). The parts are fixed by integrated hooks. The hooks serve for disconnection, if you want to wash or relocate the grids. Inroad wedges and corners provide safe over-crossing and walking.
- The grids are resistant to most of oils, acids and other chemicals as well as temperatures ranging from -10 °C to +80 °C. The grids are health non-obnoxious and 100% recyclable.



TYPE	NAME	DIMENSIONS w x d x h (mm)	COLOUR
4152	Floor grid	600 x 600 x 15	beige
6479	Work Deck Tile Blue	1,200 x 600 x 25	blue
6480	Inroad edge	width 600	blue
6481	Inroad corner	-	blue

