

UNREELING STANDS



Unreeing stands for rolled packing materials

- First of all their use can be found in your packaging and shipping centres where corrugated paperboard, wrapping paper, PE wrap, bubble or foam wrap etc. are used.
- Steel frame from square sections.
- Galvanized supporting bar with the rolled material conical fixing for accurate grip of internal diameter of husks.
- Intended for roles 1,000–1,600 mm long with their maximum weight 80 kg.

- Versions:
- horizontal unrolling stand under a table for one winding
 - horizontal unrolling stand for one winding
 - horizontal unrolling stand for two windings.



Type: 7356/100, 7356/125, 7356/160 Type: 7357/100, 7357/125, 7357/160 Type: 7358/100, 7358/125, 7358/160

	stand for one winding under the table			stand for one winding			stand for two windings		
Max. working width (mm)	1,000	1,250	1,600	1,000	1,250	1,600	1,000	1,250	1,600
Max. diameter of winding (mm)	650			1,000			900		
Max. weight (kg)	80			80			80		
Dimensions (mm)	1,400 x 805 x 600	1,650 x 805 x 600	2,000 x 805 x 600	1,400 x 805 x 900	1,650 x 805 x 900	2,000 x 805 x 900	1,400 x 805 x 1,500	1,650 x 805 x 1,500	2,000 x 805 x 1,500
Weight (kg)	15	16	17	17	18	19	22	23	25
Type	7356/100	7356/125	7356/160	7357/100	7357/125	7357/160	7358/100	7358/125	7358/160