

# PALLET TRUCKS BATTERY TRUCKS

## Low-lift pallet truck ▼ with accumulator

**Type: 3458**

- Low-lift pallet truck with accumulator travel is constructed on the basis of standard pallet trucks.
- One of this truck advantages is its battery travel, which can be used mainly while working in hard working conditions.
- Travel speed regulation is non-polar like in case of high-lift and low-lift accumulator trucks.
- Extra load capacity of the truck with accumulator travel 1,500 kg.
- Engine 0.4 kW, battery 12 V / 40 Ah.

- Truck is equipped with electromagnetic brake.



## Truck BT 2300 – polyur. singel ▼

**Type: 4695**

- Easy operating and light pumping for low muscular stress.
- Very safe with impaired accident risk.
- Provided with bushes as well as lubricating cans for effective maintenance.
- Sensitive starting controllable with fingertips.
- Rustless by-pass valve provides reliable control of hydraulics.
- Wide wheels for easy travel.
- The truck is solid, robust and light due to high-strength steel used for chassis.
- Demonstrably lowest operating costs in the market.



## Truck with quicklifting

**Type: 4696**

- The forks reach a pallet with first pumping and lift a load within a second.
- Fit for the use with great quantity of pallets.

## Truck with easy start ▼

**Type: 4697**

- The truck reduces your effort with manipulation with heavy pallets by 70% compared with common types.
- The system operates in both directions of a travel and is activated by a lever on a control handle. Its principle is to get over heavy load inertia and save labour of operator in particular at the start and getting over irregularities.
- Unique solution for demanding applications.
- Easy and precise positioning of heavy loads.
- Smooth start on uneven surfaces and sills.
- Very ergonomic solution, reduces arm, shoulder and back strain.
- Higher productivity.
- Directing wheel – polyurethane, Ø 175 x 60 mm.
- Wheels in forks – nylon, Ø 85 x 100 mm.



TYPE	NAME	WHEELS	WIDTH / LENGTH OF FORKS (mm)	MAX. LIFT (mm)	WEIGHT (kg)	LOAD CAPACITY (kg)
4695	Truck BT 2300	polyurethane	520 / 1,150	200	63	2,300
4696	Truck with quicklifting	polyurethane	520 / 1,150	200	63	2,300
4697	Truck with easy start	polyurethane	520 / 1,150	200	63	2,300
3458	Accumulator battery pallet truck	polyurethane	540 / 1,150	200	160	1,500

## El. handle high-lifting truck ▼

**Type: 4694**

- Can be used as a handy el. stacker. Ideal for manipulation in shops, for lifting of low-weight loads.
- Its small size (chassis width is only 700mm) makes manipulation easy in narrow spaces.

- The truck is provided with an integrated charger with maintenance-free gel batteries. The truck can be used also as a working table.
- Provided with a Simplex pole, lifting height 1580 mm.



**BT**  
MADE IN SWEDEN

## El. handle low-lifting truck

**Type: 4693**

- Can be used wherever common pallet trucks are used on a regular basis.
- Its low weight and small size facilitate handling in narrow spaces.
- Easy handling and high stability due to five-point solution of contact with the floor.
- The truck is provided with an integrated charger. Chassis 700 mm is narrower than EUR pallet. Truck length is just 420mm (without forks). Drive-on wheels on fork points are included in standard equipment.



**BT**  
MADE IN SWEDEN

TYPE	4693	4694
Loading capacity (kg)	1,300	1,000
Weight without batter (kg)	200	420
Travelling speed (km/hr) with/without	4/5.5	4.3/5.4
Wheels	polyurethane/Vulkollan	polyurethane/Vulkollan
Service/parking brake	electromagnetic	electromagnetic
Battery capacity (Ah)	50	63
Battery weight (kg)	2 x 20	2 x 23
Tension (V)	2 x 12	2 x 12