CONTAINERS FOR SOLID HAZARDOUS WASTE



- Suitable for storage and transport of solid and pastelike substances.
- Stackable in three layers.
- Structure from steel beams and plates, adapted for handling with a crane and also fork lift truck, lid provided with foam rubber gasket, arrested in open position.
- Pocket for accompanying documents.
- They are also used in the system of eco-container carriers, mobile collection points and the like.
- Surface finish of interior and exterior can be provided in painted version, hot-dip galvanized, with rubber lining on the customer's request.



TYPE	NAME	CAPACITY (I)	SURFACE FINISH	LOAD CAPACITY (kg)	WEIGHT (kg)	MAIN DIMENSIONS (mm)	CERTIFICATE No.
1253	KS 500	500	coated	1,000	180	1,200 x 1,000 x 910	UN11A/Y//CZ/MV-IMET4036/
1255	KS 500	500	zinc-coated	1,000	180	1,200 x 1,000 x 910	4320/1200/180kg/500l/steel3/prod.no.
1257	KS 800	800	coated	1,500	230	1,200 x 1,000 x 1,290	UN11A/Y//CZ/MV-IMET4033/
1258	KS 800	800	zinc-coated	1,500	230	1,200 x 1,000 x 1,290	3200/1730/800l/230kg/steel3/prod.no.
6049	Universal container	280	coated rubberized	180	186	1,245 x 820 x 726	