

RAIN WATER TANK ACCESSORIES

Rain water collector with a filter – automatic machine ▶

Type: 7706

- For tank filling for roofs with max. area 50 m².
- It filters rough dirt reliably (e.g. leaves).
- It prevents overflowing of full collection tanks.
- Easy to switch to summer and also winter operation.
- Equipped with a side outlet 25 mm (1") with a hose and screw joint.
- Suitable for pipes with a diameter of 70–100 mm



Technical specification:
 Height: 115 mm
 Diameter: 130 mm
 Roof max. area: 50 m²



Connection: 25 mm (1")
 For pipes with a diameter: 70–100 mm

Rain water collector with a filter – automatic machine de luxe ▶

Type: 7707

- For tank filling for roofs with max. area 80 m².
- It filters rough dirt reliably (e.g. leaves).
- It prevents overflowing of full collection tanks.
- Easy to switch to summer and also winter operation.
- Equipped with a side outlet 32 mm (1 ¼") with a hose and screw joint.
- Suitable for pipes with a diameter of 70–100 mm.



Technical specification:
 Height: 150 mm
 Diameter: 150 mm
 Roof max. area: 80 m²



Connection: 32 mm (1 ¼")
 For pipes with a diameter: 70–100 mm

Rain water collector with a self-cleaning filter ▶

Type: 7708

- Self-cleaning filter Regendieb for rainwater cleaning for roofs with max. area of 80 m².
- It filters dirt from rainwater reliably.
- Self-cleaning filter with a fine stainless-steel filter.
- It fills the rainwater tank and prevents its overflowing.
- It can be changed to summer or winter operation easily by turning the filter insert.
- Suitable for pipes with a diameter of 70–100 mm.
- Supplied including the DN 19/32 gasket suitable for all aboveground tanks.



Technical specification:
 Height / width / depth: 250 / 150 / 200 mm
 Roof max. area: 80 m²
 Connection: DN 70 / DN 50, 32 mm (1 ¼")
 For pipes with a diameter: 70–100 mm

Rain water collector with a dirt separator ▼

Type: 7709

- Laubabscheider protection against dirt for roofs with max. area of 80 m².
- Perfect during frequent falling of leaves.
- It separates leaves and rough dirt reliably preventing pipes from clogging.
- Suitable to be used as pre-filtration.
- Easy removal of the sieve without all the filter disassembly – suitable for cleaning or in the period before freezing.
- Easy to be switched from summer to winter operation.
- Suitable for pipes with a diameter of 70–100 mm.



Technical specification:
 Height / width / depth:
 350 / 110 / 180 mm
 Roof max. area: 80 m²
 For pipes with a diameter:
 70–100 mm

Connecting hose ▼

- Hose Ø ¾" (Type: 8067-A)
- Hose Ø 1 ¼" (Type: 8067-B)
- Hose Ø 2" (Type: 8067-C)

